

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cquartz Lite

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coatings.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	carparts GmbH	
Street:	Vietorstraße 87	
Place:	D-51103 Köln	
Telephone:	+49 (0)221 28 58 58 -58	Telefax: +49 (0)221 28 58 58 -99
e-mail:	info@carparts-koeln.de	
Responsible Department:	info@carparts-koeln.de	

1.4. Emergency telephone number:

+49 (0)221 28 58 58 -58 (9:00-17:00 Mo-Fr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1B

Reproductive toxicity: Repr. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha

Stoddard solvent; Low boiling point naphtha - unspecified

toluene

Trimethoxy(1H,1H,2H,2H-heptadecafluorodecyl)silane

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 2 of 16

Signal word: Danger

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to local/regional/national/international regulations.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			20 - 40 %
	265-150-3	649-327-00-6		
	Flam. Liq. 3, Asp. Tox. 1; H226 H304 EUH066			
8052-41-3	Stoddard solvent; Low boiling point naphtha - unspecified			1 - 20 %
	232-489-3	649-345-00-4		
	Flam. Liq. 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H372 H304 H411			
108-88-3	toluene			1 - 20 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
546-68-9	Titanium tetraisopropanolate			1 - 10 %

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 3 of 16

	208-909-6			
	Flam. Liq. 3, Eye Irrit. 2; H226 H319			
107-46-0	Hexamethyldisiloxane			1 - 10 %
	203-492-7			
	Flam. Liq. 2, Aquatic Acute 1, Aquatic Chronic 2; H225 H400 H411			
1330-20-7	xylene			1 - 10 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Aquatic Chronic 2; H226 H332 H312 H315 H411			
83048-65-1	Trimethoxy(1H,1H,2H,2H-heptafluorodecyl)silane			1 - 10 %
	Skin Corr. 1B; H314			
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine			< 2 %
	217-164-6			
	Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 2; H332 H318 H317 H411			
100-41-4	ethylbenzene			< 2 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Carc. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H351 H332 H373 H304			
1112-39-6	dimethoxydimethylsilane			< 1 %
	214-189-4			
	Flam. Liq. 2, Repr. 2; H225 H361			
91-20-3	naphthalene			< 0,5 %
	202-049-5	601-052-00-2		
	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410			
67-56-1	methanol			< 0,5 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 4 of 16

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam.
In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 5 of 16

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust ventilation at critical locations.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases.

Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides.

Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Protect against: UV-radiation/sunlight. heat. Humidity frost.

storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
91-20-3	Naphthalene	10	50		TWA (8 h)	EU
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 6 of 16

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. (DIN EN 374)

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 7 of 16

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid.	
Colour:	transparent	
Odour:	like petroleum	
pH-Value:		not determined

Changes in the physical state

Melting point:		not applicable
Initial boiling point and boiling range:		108 °C
Flash point:		43 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:		not determined
Upper explosion limits:		not determined
Ignition temperature:		not determined
Decomposition temperature:		not determined

Oxidizing properties

none.

Vapour pressure: (at 20 °C)		not determined
Density:		not determined
Water solubility:		miscible.

Solubility in other solvents

not determined

Viscosity / dynamic: (at 40 °C)		not determined
Viscosity / kinematic: (at 20 °C)		not determined
Vapour density:		not determined
Evaporation rate:		not determined
Solvent separation test:		not determined
Solvent content:		not determined

9.2. Other information

Solid content:		not determined
----------------	--	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 8 of 16

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat. moisture.
In use may form flammable/explosive vapour-air mixture.
Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.
The product has not been tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >2000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) aerosol	LC50 5,61 mg/l	Rat	ECHA Dossier	
108-88-3	toluene				
	oral	LD50 >5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	ECHA Dossier	
1330-20-7	xylene				
	oral	LD50 (3523) mg/kg	Rat.	ECHA Dossier	
	dermal	LD50 >1700 mg/kg	Rabbit	RTECS	
	inhalation (4 h) vapour	LC50 [27,6-29,1] mg/l	Rat.	ECHA Dossier	
	inhalation aerosol	ATE 1,5 mg/l			
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine				
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 (3500) mg/kg	Rat.	GESTIS	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 9 of 16

	dermal	LD50 mg/kg	>20000	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat.	ECHA Dossier	
	inhalation aerosol	ATE	1,5 mg/l			
91-20-3	naphthalene					
	oral	ATE mg/kg	500			
67-56-1	methanol					
	oral	ATE mg/kg	100			
	dermal	ATE mg/kg	300			
	inhalation vapour	ATE	3 mg/l			
	inhalation aerosol	ATE	0,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (N-(3-(trimethoxysilyl)propyl)ethylenediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Stoddard solvent; Low boiling point naphtha - unspecified)

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

Further information

Solvent:

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting. Nausea.

Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information**12.1. Toxicity**

The product has not been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha					
	Acute fish toxicity	LC50 8,2 mg/l	LL50:	96 h Pimephales promelas	ECHA Dossier	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 10 of 16

	Acute algae toxicity	ErC50 3,1 mg/l	EL50:	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 4,5 mg/l	EL50:	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC 2,6 mg/l	NOELR:	21 d	Daphnia magna	ECHA Dossier	
108-88-3	toluene						
	Acute fish toxicity	LC50 mg/l	(5,5)	96 h	Oncorhynchus kisutch	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	12,5	72 h	Pseudokirchneriella subcapitata	MSDS external	
	Acute crustacea toxicity	EC50 mg/l	(3,78)	48 h	Ceriodaphnia dubia	ECHA Dossier	
	Fish toxicity	NOEC	1,4 mg/l	40 d	other	MSDS external	
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia Dubia	MSDS external	
	Acute bacteria toxicity	(134 mg/l)		3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier	
100-41-4	ethylbenzene						
	Acute fish toxicity	LC50 mg/l	(5,1)	96 h	Menidia menidia	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	(3,6)	96 h	Selenastrum capricornutum	GESTIS	
	Acute crustacea toxicity	EC50 mg/l	(1,8-2,8)	48 h	Daphnia magna	ECHA Dossier	
	Acute bacteria toxicity	(7,7 mg/l)			Skeletonema costatum	ECHA Dossier	
67-56-1	methanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	DIN 38412 Teil 11

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
108-88-3	toluene			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	100%	14	MSDS external
	Readily biodegradable (according to OECD criteria).			
100-41-4	ethylbenzene			
	ISO 14593-CO2-Headspace Test	79	28	ERCHA Dossier

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 11 of 16

	Easily biodegradable (concerning to the criteria of the OECD)			
67-56-1	methanol			
	other guideline	76%	20	ECHA Dossier
	Easily biodegradable (concerning to the criteria of the OECD)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
1330-20-7	xylene	3,82
100-41-4	ethylbenzene	3,6
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	13,2-90	Fish	MSDS external
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

110198 WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); other wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

110198 WASTES FROM CHEMICAL SURFACE TREATMENT AND COATING OF METALS AND OTHER MATERIALS; NON-FERROUS HYDRO-METALLURGY; wastes from chemical surface treatment and coating of metals and other materials (for example galvanic processes, zinc coating processes, pickling processes, etching, phosphating, alkaline degreasing, anodising); other wastes containing hazardous substances; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 12 of 16

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 13 of 16

Marine pollutant:	NO
Special Provisions:	955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1139
14.2. UN proper shipping name:	Coating solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Special Provisions:	A3
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

See section 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 48: toluene

Entry 69: methanol

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3, 40, 48 (toluene: Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.), 69 (Methanol: Shall not be placed on the market to the general public after 9 May 2019 in windscreen washing or defrosting fluids, in a concentration equal to or greater than 0,6 % by weight.)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 14 of 16

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information**Changes**

Rev. 1.00; Initial release 04.03.2019
Rev. 2.00; 05.03.2019, Changes in chapter: 3.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
AGW: Arbeitsplatzgrenzwert
AVV: Abfallverzeichnisverordnung
CAS Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
DNEL: Derived No Effect Level
d: day(s)
EAKV: Europäisches Abfallverzeichnis gemäß Entwurf Abfallverzeichnisverordnung
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NLP: No-Longer Polymers
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 15 of 16

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS Technische Regeln fuer Gefahrstoffe

UN: United Nations

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1B; H317	Calculation method
Repr. 2; H361d	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Cquartz Lite

Revision date: 05.03.2019

Product code:

Page 16 of 16

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)